



OPUS™ PRE AMPLIFIER



REFERENCE HERITAGE REFINED

Experience audio at its finest with a pre-amplifier that combines elegant design, advanced engineering, and exceptional versatility. Cascading technology developed for our flagship models, it delivers a highly engaging and natural music performance.

Powered with the Celsius mains transformer and dedicated built-in Pulsus phono stage, powered by its own transformer, reveals the full realism and musicality of your vinyl collection. With support for up to four line-level sources, plus both RCA and XLR connections, integration is effortless. Intuitive front-panel controls make source selection simple, allowing seamless switching between devices while maintaining the highest standards of sound quality.

SPECIFICATIONS	
PHONO INPUTS	1 x RCA
GAIN	48dB-60dB-70dB
INPUT RESISTANCE	100R-300R-500R-1K-5K-10K-47K
INPUT CAPACITANCE	100pF-200pF-500pF
DISTORTION	LESS THAN 0.001%
RIAA ACCURACY	5Hz-70Hz±0.5dB
NOISE (A WEIGHTED)	MM-81dB MC-67dB
CHANNEL SEPARATION	<-85dB 5Hz - 20KHz
LINE INPUTS	2 x XLR 2 x RCA
NOMINAL SENSITIVITY	340 mV
INPUT IMPEDANCE	33kΩ (XLR) 82kΩ (RCA)
FREQUENCY RESPONSE	5Hz-OVER 80KHz±0.5dB
MAXIMUM INPUT	9.7 V RMS
SIGNAL/NOISE RATIO	100dB (XLR) 103dB(RCA)
TOTAL HARMONIC DISTORTION(THD)	<0.0005%
PRE-AMPLIFIER OUTPUT	1 x XLR 1xRCA
NOMINAL OUTPT LEVEL	11V
OUTPUT IMPEDANCE	47Ω
DIMENSIONS	471 x 472 x 122mm (WxDxH)
NET WEIGHT	19.2 KG (43 Lbs)



Bicton Industrial Park, Kimbolton, Huntingdon, Cambs. PE28 0LW ENGLAND
Tel: +44 (0)1480 869900 / Web: www.avidhifi.co.uk / Email: info@avidhifi.co.uk